



- ① Refer to SI-881 for sign details.
- ② Equip all vehicles with an amber revolving light or amber strobe light.
- ③ This arrow board may be operated in a four-corner caution mode.
- ④ For roadways with a posted speed limit of 60 mph or greater before road work:
 - Place SPEED LIMIT 55 signs prior to the lane closure as shown.
 - Remove or cover all existing signs that conflict with 55 mph speed limit while 55 mph speed limit is in effect.
 - For traffic control zones lasting more than 4 hours, a Speed Feedback Sign may be placed at the end of the merge taper.

Possible Contract Item:
Traffic Control

LEGEND

- ➔ Direction Of Traffic
- † Traffic Sign
- x Drum
- 42" Channelizer
- ▨ Truck-Mounted Attenuator (TMA)
- ⦿ Speed Feedback Sign
- ⬅ Arrow Board
- ▨ Work Area

When the Average Daily Traffic (ADT) exceeds 20,000 vehicles per day or when a traffic queue extends beyond the advanced signing, place RIGHT/LEFT LANE CLOSED 4 MILES and RIGHT/LEFT LANE CLOSED 2 MILES signs (W20-5) on both sides of the roadway 4 miles and 2 miles in advance of the lane closure, respectively, as appropriate.

REVISIONS: New.

IOWA DOT

STANDARD ROAD PLAN

REVISION 4-21-20

TC-415

SHEET 1 of 1

APPROVED BY DESIGN METHODS ENGINEER

SHORT TERM LANE CLOSURE WITH TMA