

PLAN VIEW - TOP & BOTTOM OF APRON REINFORCING BARS

NOTES:

1. BAR SPACINGS AND POSITIONS SHOWN ARE SIMILAR FOR ALL SIZES OF HEADWALLS IN THIS STANDARD.
2. WINGWALL BARS CONSISTENTLY REFERENCED FROM END OF WING FOR ALL HEADWALLS.
3. TOP TRANSVERSE FLOOR BARS ARE 4" FROM THE BACK OF THE PARAPET FOR ALL HEADWALLS.
4. THERE ARE NO 5c8 BARS IN THE 4' & 5' HEIGHT HEADWALLS.
5. 4c2 BARS USED ONLY IN THE 9', 10', 11' & 12' HEIGHT HEADWALLS.
6. FOR DIMENSION TABLE SEE SHEET TRH 0-1-12.
7. FOR REINFORCING IN CURTAIN WALL SEE CURTAIN WALL DETAILS SHEET TRH 0-3-12.

LATEST REVISION DATE

APPROVED BY BRIDGE ENGINEER

Iowa Department of Transportation
Highway Division

STANDARD DESIGN

TRIPLE REINFORCED CONCRETE BOX CULVERTS

APRIL, 2012

FLARED WING HEADWALLS

0° SKEW

TRH 0-2-12

ENGLISH\REDSIGNED\TRIPLECULVERTS.DGN - TRH 0-2-12 - THIS SHEET ISSUED 04-12.