



* DIMENSION RESTRICTIONS APPLY TO MAIN SIGN PANEL AND ANY SUPPLEMENTAL SIGN PANELS THAT MAY BE PRESENT.

** CENTER THE MAIN SIGN PANEL VERTICALLY ON THE TRUSS IF THE SUPPLEMENTARY SIGN PANEL LENGTH IS LESS THAN HALF THE LENGTH OF THE MAIN SIGN PANEL, OTHERWISE CENTER THE COMBINED HEIGHT OF THE MAIN SIGN PANEL AND SUPPLEMENTARY SIGN PANEL VERTICALLY ON THE TRUSS.

*** USE $L 6 \times 3 \frac{1}{2} \times \frac{1}{2}$ FOR SIGN HEIGHT OVER 10'-0" TO 20'-0" AND $L 5 \times 3 \times \frac{1}{2}$ FOR SIGN HEIGHT OF 10'-0" OR LESS. A TOTAL SIGN HEIGHT GREATER THAN 20'-0", SIGN VERTICAL CANTILEVER LENGTH GREATER THAN 6'-7", AND/OR SIGN SUPPORT ANGLE HORIZONTAL SPACING GREATER THAN 5'-0" REQUIRES APPROVAL BY THE OFFICE OF BRIDGES AND STRUCTURES.

03-2018
LATEST REVISION DATE

APPROVED BY BRIDGE ENGINEER

IOWA DOT Highway Division

STANDARD DESIGN

STEEL CANTILEVER SIGN TRUSS

JULY, 2017

SIGN ATTACHMENT DETAILS

SCST-07-17