



Triple Reinforced Concrete Box Culvert Standards

General Notes:

- The RCB culvert sections are designed for HL-93 live load and earth fills of varying heights.
- Vertical earth pressure, $E_V = 0.120 \text{ kcf}$.
- Horizontal earth pressure, $E_{Hmax} = 0.060 \text{ kcf max}$, $E_{Hmin} = 0.030 \text{ kcf}$.
- The RCB culvert sections are designed for Class 1 exposure conditions except:
 - Class 2 exposure condition is utilized for the slab design in 0' fill instances.
- All slab and floor reinforcing steel is to be supported at intervals of not more than 3'-0" in either direction as outlined in the Standard Specifications.
- The clear distance from face of concrete to near edge or end of reinforcing bar to be 2" unless otherwise noted.
- Except for dowel bars 5r1 in slab, longitudinal reinforcing is not to extend thru the construction joints.
- Floor of barrel is to be finished smooth. Sides of footing are to be formed to insure correct line and grade.
- The permissible construction joint at the top of the walls may be lowered at the Contractor's option with Engineer's approval.
- The reinforcement supplied for this structure shall be Grade 60 reinforcement in accordance with the Standard Specifications. The design stresses are based on ASTM A706 Grade 60 reinforcement.
- The vertical bars in the walls may be spliced above the footing at the Contractor's option as follows:

| | | | | | | |
|-----------------------|-----|-----|-----|-----|-----|-----|
| Bar Size Number | 4 | 5 | 6 | 7 | 8 | 9 |
| Minimum Splice Length | 20" | 24" | 29" | 34" | 38" | 47" |

- This splice, if used, will be at the Contractor's expense.
- Reinforcing bar clearances will be as follows:
 - Edge clearances: 2" except
 - Top of floor 2½" to near transverse reinforcing bar
 - Bottom of floor 3½" to near transverse reinforcing bar
 - End clearances:
 - Vertical top 2"
 - Vertical bottom 3" or 3½" if overall height of the culvert is not to a full inch
 - Transverse 2"
 - All construction joints shall be formed with a beveled keyway except at bell joints.
 - All beveled keyways shall be centered.
 - Keyway size shall be 2"x4" except as follows:
 - Keyway between the floor and wall shall be 2"x6" when the wall is greater than 10 inches wide.
 - Keyway dimensions shown on the plans are based on nominal dimensions unless stated otherwise. In addition, the bevel used on the keyway shall be limited to a maximum of 10 degrees from vertical.
 - If 0' of fill is specified, details for paving notch and reference to epoxy coating of slab reinforcing steel, if applicable, shall be included in the final plans.
 - All dimensions are in feet and inches unless otherwise noted or shown.
 - See current Standard Specifications regarding concrete form removal.
 - These culvert standards label all reinforcing steel with English notation (5a1 is ⅝ inch diameter bar). English reinforcing steel received in the field may display the following "bar designation". The "bar designation" is the stamped impression on the reinforcing bars, and is equivalent to the bar diameter in millimeters.

| | | | | | | |
|-----------------|----|----|----|----|----|----|
| English Size | 4 | 5 | 6 | 7 | 8 | 9 |
| Bar Designation | 13 | 16 | 19 | 22 | 25 | 29 |

- In the event the slab thickness at the barrel end section exceeds 18 inches, the culvert parapet shall extend a minimum of 6 inches above the top of the culvert slab. Refer to the Culvert Design Manual for instructions. These details are to be included in the design plans to address these situations.

Specifications:

Design:
AASHTO LRFD Bridge Design Specifications, 8th Ed., Series of 2017.

Construction:
Iowa Department of Transportation Standard Specifications for Highway and Bridge Construction, current series, plus applicable General Supplemental Specifications, Developmental Specifications, Supplemental Specifications and Special Provisions

Design Stresses:

Design stresses for the following materials are in accordance with the AASHTO LRFD Bridge Design Specifications, 8th Ed., Series of 2017:
Reinforcing steel in accordance with AASHTO LRFD Section 5, Grade 60.
Concrete in accordance with AASHTO LRFD Section 5, $f'_c = 4.0 \text{ ksi}$.

ENGLISHLRFDDESIGNEDTRIPLECULVERTS.DGN - TRRCB_G2-20 - THIS SHEET ISSUED 07-2020.

| | | | |
|----------------------|-----------------------------|---|-------------|
| LATEST REVISION DATE | APPROVED BY BRIDGE ENGINEER | | |
| | | Standard Design Triple Reinforced Concrete Box Culverts July, 2020 | |
| | | General Notes & Specifications | TRRCB G2-20 |