



**LEGEND**

- ⊣ Traffic Sign
- 42" Channelizer or Vertical Panel
- ▨ Work Area
- ← Direction of Traffic

SPEED LIMIT (mph)	A	B	C <sup>②</sup>	T
35 or less	500'	250'	40'	100'
40 - 45	700'	350'	80' ①	200'
50 or greater	1000'	500'	100' ①	200'

When a shoulder drop-off of 6" or less exists, install a SHOULDER DROP-OFF sign, as shown.

When a shoulder drop-off greater than 6" exists, install a NO SHOULDER sign, as shown.

Where the length of a shoulder drop-off exceeds 1000 feet, construct a temporary fillet meeting the requirements of Article 1107.09 of the Standard Specifications.

Drop-offs greater than a nominal 10" will not be allowed during non-working hours.

- ① Spacing = 40' when shoulder drop-offs are present.
- ② For work areas less than 200' long, use channelizers spaced at 20' centers or use a vehicle with an amber revolving light or amber strobe light.

Contract Item:  
Traffic Control

<p>Iowa Department of Transportation</p> <p><b>STANDARD ROAD PLAN</b></p> <p>REVISIONS: Modified speed limit table values and variables. Revorded notes.</p> <p><i>Deanna Macfild</i> APPROVED BY DESIGN METHODS ENGINEER</p>	REVISION
	2   10-21-08
	<b>TC-202</b> SHEET 1 of 1

**SHOULDER CLOSURE**