



- LEGEND**
- Traffic Sign
 - Flagger
 - Work Area
 - Type III Barricade
 - Direction of Traffic

SPEED LIMIT (mph)	A	F and G Range (3)	F + G Max.
35 or less	250'	250'-3250'	3500'
40 - 45	350'	350'-3350'	3700'
50 or greater	500'	500'-3500'	4000'

- ① A vehicle with an amber revolving or an amber strobe light may be substituted for the Type III barricade.
- ② A second flagger shall be required:
If the flagger's view of approaching traffic in the open lane is less than 1/4 mile or the work site is in an area of restricted sight distance (such as a "No Passing" zone); or
If excessive traffic delays are encountered.
- ③ F and G distances are to remain as near minimum values as work permits. However, to be able to move the work area without moving the advance signing, F and G distances may be varied within the limits of the table. Maximum movement can be achieved by setting one F or G value at the minimum and the other value at its maximum.

Contract Items:
Traffic Control
Flaggers

Iowa Department of Transportation STANDARD ROAD PLAN <small>REVISIONS: Modified speed limit table values and variables.</small>	<small>REVISION</small> 1 10-16-07
	TC-212 <small>SHEET 1 of 1</small>
<small>APPROVED BY DESIGN METHODS ENGINEER</small> <i>Deanna Macfist</i>	
SPOT LOCATION LANE CLOSURE WITH FLAGGERS	