



LEGEND

- ⊥ Traffic Sign
- ✕ Drum
- 42" Channelizer or Vertical Panel
- ▤ Arrow Panel
- Temporary Floodlighting
- ▬ Temporary Crash Cushion
- ▨ Work Area
- ← Direction of Traffic

SPEED LIMIT (mph)	D	E	M	T
45 - 50	45'	300'	630'	100'
55 - 60	55'	400'	770'	100'
65 - 70	65'	500'	910'	100'

When the Average Daily Traffic (ADT) exceeds 20,000 vehicles per day or when a traffic queue extends beyond the advanced signing, place RIGHT LANE CLOSED 4 MILES and RIGHT LANE CLOSED 2 MILES signs (W20-5) on both sides of the roadway 4 miles and 2 miles in advance of the lane closure, respectively.

① For roadways with a posted speed limit of 60 mph or greater before road work:

Place SPEED LIMIT AHEAD sign and SPEED LIMIT 55 sign prior to the lane closure as shown. Place SPEED LIMIT 65 or 70 beyond the work area as shown.

All existing signs that conflict with 55 mph speed limit shall be removed or covered while 55 mph speed limit is in effect.

② Refer to RD-65 for sign details.

- Contract Items:**
- Traffic Control
 - Pavement Marking Items
 - Painted Symbols and Legends
 - Pavement Markings Removed
 - Symbols and Legends Removed
 - Temporary Barrier Rail
 - Temporary Floodlighting
 - Temporary Crash Cushions

- Tabulation:**
- 108-22
 - 108-27
 - 108-29
 - 108-30
 - 108-33

Iowa Department of Transportation

STANDARD ROAD PLAN

REVISIONS: Changed contract item from Painted Pavement Markings to Pavement Marking Items and added tab number 108-30.

Deanna McFalls
APPROVED BY DESIGN METHODS ENGINEER

REVISION

3 | 04-21-09

TC-421

SHEET 1 of 1

LANE CLOSURE WITH TBR