



GENERAL NOTES:

The contractor shall furnish and install posts for Delineators and Type 2 Object Markers. Post lengths shall be sufficient to provide a minimum of 0.8 meters of embedment when installed at the specified mounting height.

Price bid for "Delineators" and "Object Markers" of the type specified per unit shall be full compensation for all installation work and materials necessary as detailed herein. When Delineators and Object Markers are required with guardrail installations, the Delineators and Object Markers will be included with the price bid for "Installation of Guardrail".

- ① "OM2-3YH" I.D.O.T. Designation. "Type 2 Object Marker" MUTCD Designation.
- ② Other tamper resistant type fasteners may be used with the approval of the Engineer.
- ③ Delineators shall be placed at a constant distance from pavement edge as required on the project plans.
- ④ When shoulder width is 1.8 meters or less, delineators shall be a minimum of 2.5 meters from edge of pavement.
- ⑤ 0.8 meters minimum embedment.
- ⑥ Posts shall be centered when used in raised median island.

All dimensions given in millimeters unless noted.

METRIC VERSION	M Iowa Department of Transportation Highway Division	
	STANDARD ROAD PLAN	RE-7
	REVISION: Include Yellow Delineators, Center Post In Raised Median.	
	<i>William J. Steen</i> APPROVED BY DESIGN METHODS ENGINEER	REVISION NO. 14 REVISION DATE 04-15-03
DELINEATORS AND OBJECT MARKERS		