



TYPICAL SHOULDER SECTION

TABLE OF DESIGN QUANTITIES (3) (4)				
TYPE 'A' OR TYPE 'B' GRANULAR SHOULDER				
(T)	(E) = 1.2 m	(E) = 1.8 m	(E) = 2.4 m	(E) = 3.0 m
	Mg/Sta	Mg/Sta	Mg/Sta	Mg/Sta
150	68.51	88.76	109.01	129.26

GENERAL NOTES:

Earth shoulder fill shall be placed in accordance with the current Standard Specifications for "Granular Shoulders." Refer to detail project plans for estimated quantity of material required. Earth material shall be obtained from adjacent areas at the direction of the Engineer.

Any special shaping of subgrade necessary prior to construction of Type 'A' or Type 'B' granular shoulder shall be accomplished as directed by the Engineer. Any material removed due to special shaping may be used as earth fill, Class 10 excavation, Class 13 excavation, or on other suitable areas on the project as approved by the Engineer.

Natural subgrade prior to placement of Type 'A' or Type 'B' granular shoulder material shall be adequately compacted and smoothed for proper construction of shoulder.

- (1) Refer to Typical Cross Section and detail project plans for exact shape and dimensions of adjacent pavement.
- (2) Refer to Typical Cross Sections and detail project plans for details of slope variation through super-elevated curves.
- (3) One shoulder per station.
- (4) Quantities have been determined on the basis of a design density of 2250 kilograms per cubic meter and have been adjusted for the flatter than 6:1 foreslope at the outside edge. Quantities indicated are for design purposes and may be adjusted at the time of construction if so directed by the Engineer.

All dimensions given in millimeters unless noted.

<b>METRIC VERSION</b>	<b>M</b> Iowa Department of Transportation Highway Division	
	<b>STANDARD ROAD PLAN RJ-26D</b>	
	REVISION: Changed ACC to HMA	REVISION NO. 5
	APPROVED BY: <i>William J. Steen</i> DESIGN METHODS ENGINEER	REVISION DATE 10-02-01
TYPE 'A' AND 'B' GRANULAR SURFACED SHOULDER (ADJACENT TO HMA PAVEMENT)		