



LEGEND

- Traffic Sign
- 42" Channelizer or Vertical Panel
- Work Area
- Direction of Traffic

| SPEED LIMIT (mph) | A | B | C ^② | T |
|-------------------|-------|------|-------------------|------|
| 35 or less | 500' | 250' | 40' | 100' |
| 40 - 45 | 700' | 350' | 80' ^① | 200' |
| 50 or greater | 1000' | 500' | 100' ^① | 200' |

When a pavement edge drop-off exists, install a SHOULDER DROP-OFF sign.

Pavement edge drop-offs greater than a nominal 10 inches will not be allowed during non-working hours.

Shoulder edge drop-offs shall be mitigated according to Article 1107.08.K2 of the Standard Specifications.

^① When the length of a pavement edge drop-off is 1000 feet or less, the temporary fillet requirement of Article 1107.08 of the Standard Specifications does not apply.

Space devices at 40 feet.

^② For work areas less than 200 feet long, use channelizers spaced at 20 foot centers or use a vehicle with an amber revolving light or amber strobe light.

Possible Contract Item:
Traffic Control

| | | |
|--|---------------|----------|
| STANDARD ROAD PLAN | REVISION | |
| | 3 | 04-20-10 |
| | TC-202 | |
| | SHEET 1 of 1 | |
| REVISIONS: Changed shoulder signs, general note, and title. Updated signs. | | |
| APPROVED BY DESIGN METHODS ENGINEER | | |
| SHOULDER CLOSURE (ONE LANE) | | |