



END  
ROAD WORK  
G20-2A  
48" X 24"

ROAD  
WORK  
AHEAD  
W20-1  
48" X 48"

ONE LANE  
ROAD  
AHEAD  
W20-4  
48" X 48"

W20-Ta  
48" X 48"

END  
ROAD WORK  
G20-2A  
48" X 24"

- LEGEND**
- ▬ Traffic Sign
  - Flagger
  - 42" Channelizer or Vertical Panel
  - ▨ Work Area
  - ← Direction of Traffic

SPEED LIMIT (mph)	A	C	E	F and G Range	F + G Max.	H Max.	T
35 or less	250'	40'	0'-200'	500'-3000'	3500'	2000'	50'
40 - 45	350'	80'	0'-200'	700'-3000'	3700'	2000'	100'
50 or greater	500'	100'	200'-300'	1000'-3000'	4000'	2000'	100'

- ① Keep F and G distances as near to minimum values as work permits. However, to allow advancement of the work area without moving signs, F and G distances may be varied within the limits of the table. Maximum movement can be achieved by setting one F or G value at the minimum and the other value at its maximum.
- ② If length of work area exceeds 1/4 mile, use TC-214.

Contract Items:  
Traffic Control  
Flaggers

<p>Iowa Department of Transportation</p> <p><b>STANDARD ROAD PLAN</b></p> <p>REVISIONS: Modified speed limit table values and variables.</p> <p><i>Deanna Macfadyen</i> APPROVED BY DESIGN METHODS ENGINEER</p>	<p>REVISION</p> <p>2 10-21-08</p>
	<p><b>TC-213</b></p> <p>SHEET 1 of 1</p>
	<p><b>LANE CLOSURE WITH FLAGGERS</b></p>