



LEGEND

- Traffic Sign
- Type III Barricade
- Temporary Floodlighting
- Type 'B' High-Intensity Flashing Warning Light
- Traffic Signal
- Direction of Traffic

SPEED LIMIT (mph)	A
35 or less	250'
40 - 45	350'
50 or greater	500'

Set signal timing as follows: For traffic from all directions, set the yellow indication at approximately 5 seconds and the all-red clearance interval at approximately 2 seconds. Set the minimum green interval on the main road at 20 seconds. Set the green interval for haul road traffic at 12 seconds but may be extended up to a maximum of 30 seconds.

- 1 Locate the stop bars 70 feet in advance of each lane's nearest signal head.
- 2 Required only if haul road is used during nighttime hours.
- 3 When the equipment crossing is not in use, place Type III Barricades as shown, and cover SIGNAL AHEAD and STOP HERE ON RED signs.

Possible Contract Items:
Pavement Marking Items
Pavement Markings Removed
Traffic Control
Temporary Floodlighting
Temporary Traffic Signals

Possible Tabulations:
108-22
108-27
108-28

 STANDARD ROAD PLAN	REVISION	
	3	10-19-10
	TC-271	
	SHEET 1 of 1	
REVISIONS: Remove requirement of span-wire mounted signal (spec covers this and alternate). Updated language.		
 APPROVED BY DESIGN METHODS ENGINEER		
SIGNALIZED EQUIPMENT CROSSING		