



**SPECIAL PROVISIONS
FOR
PLANTS**

**Johnson County
RT-C052(105)--9H-52
NRT-C052(111)--9G-52**

**Effective Date
October 17, 2017**

THE STANDARD SPECIFICATIONS, SERIES 2015, ARE AMENDED BY THE FOLLOWING MODIFICATIONS AND ADDITIONS. THESE ARE SPECIAL PROVISIONS AND THEY SHALL PREVAIL OVER THOSE PUBLISHED IN THE STANDARD SPECIFICATIONS.

PART 1 DESCRIPTION.

A. Section Includes.

1. Plant Material and Planting
2. Establishment Period for Plant Material
3. Watering
4. Shredded Hardwood Bark Mulch
5. Washed River Rock Mulch

B. Submittals.

1. Submit copy of current certification that the Supplier is an Iowa Department of Agriculture and Land Stewardship Certified Nursery Dealer or Grower prior to starting work.
2. Prior to final acceptance, submit written maintenance instructions recommending procedures for maintenance of all plant material types, including watering, insect and disease control, fertilizing, pruning, tree wrapping, and staking.
3. When requested, provide certification stating container-grown material has been grown in the container for no less than 1 year.
4. Provide a sample of the proposed shredded hardwood and washed river rock mulch for approval by the Engineer.

5. When requested, submit a schedule of unit prices for each size and variety of tree, shrub, and ground cover plant specified in the contract documents.

C. Substitutions.

Where evidence is submitted that a specified plant cannot be obtained, substitution may be made upon approval of the Engineer.

PART 2 MATERIALS.

A. Plant Materials.

1. General.

- a. Ensure plant material meets the minimum requirements of size and grade as stated in the latest edition of American Standard for Nursery Stock, ANSI Z60.1.
- b. Provide all plants true to name and tagged legibly as to name according to nursery standards of practice as recommended by the American Nursery and Landscape Association. Plant names indicated comply with the latest edition of "Standardized Plant Names" as adopted by the American Joint Committee of Horticultural Nomenclature.
- c. Plants larger than those specified in the plant list with corresponding root system may be used upon approval of the Engineer.
- d. Match plants planted in rows and in groupings in form and size, unless otherwise specified in the contract documents.

2. Plant Material Quality.

- a. Provide nursery grown plants grown in the same climatic zone as the project.
- b. One-sided branching plants from tightly planted nursery rows will be rejected.
- c. Provide healthy specimens without objectionable deformities, voids, and open spaces, with well-developed branch and root systems. Ensure specimens are true to height, shape, and character of growth of the species or varieties. Provide plants showing appearance of good health and vigor.
- d. Provide plants free of the following:
 - 1) Harmful insects, insect eggs, borers, and all forms of infestation
 - 2) Plant diseases and moldy or dried roots
 - 3) Damage to trunk, bark, branches, leaders, root systems, or cut-leaders
 - 4) Defects, disfiguring knots, sunscald injuries, and frost cracks
 - 5) Rodent damage to bark and buds
- e. Plants with broken or cut back terminal leaders may be rejected.

3. Balled and Burlapped Plants.

- a. Provide firm, moist, unbroken root balls of the specified size.
- b. Broken or loose root balls will be rejected.
- c. No manufactured or artificially produced or mudded-in root balls will be accepted.
- d. A container grown plant, in lieu of a balled and bur lapped root ball, will be accepted provided it meets the specified size, complies with American Standard for Nursery Stock (ANSI Z60.1), and meets criteria for container grown plants.

4. Container Grown Plants.

- a. Grow plants in sufficiently sized container for a minimum of 1 year, with a root system developed to hold its soil together, firm, whole, and moist when taken from the container.
- b. No loose root systems in the container, root-bound, or circling of the root system will be accepted.

B. Mulch.

1. Provide hardwood and washed river rock mulch complying with the following:
 - a. Shredded bark and shredded wood mixture containing no more than 50% wood chips.
 - b. Produced by a mechanical debarker and chipping machine.
 - c. Free from leaves, twigs, dust, toxic substances, and any other foreign material.
 - d. Not in an excessively wet or decomposed condition.

2. Rock mulch.

Rock mulch to be 2 to 4 inch diameter river rock commercially available locally.

C. Backfill Material.

1. Acquire backfill material for plantings from soil excavated from the planting pit.
2. Ensure backfill material is loose, friable, and free of clods and rocks 2 inches in diameter or larger. Do not use frozen or muddy soil as backfill material.

D. Tree Wrapping Material for Winter Protection.

4 inch wide bituminous impregnated tape, corrugated or crepe paper, specifically manufactured for tree trunk wrapping, having qualities to resist insect infestation, or similar material approved by the Engineer.

E. Landscape Edge.

Provide spaded edge with motorized edger as shown in plans.

F. Water.

Provide water and watering equipment such as hoses and sprinklers. Provide water free of substances harmful to plant growth.

G. Herbicide.

Provide a granular pre-emergent herbicide as approved by the Engineer.

PART 3 CONSTRUCTION.

A. Delivery, Storage, and Handling.

1. Protect plant root systems during transportation and storage, as necessary, with wet straw, moss, or other suitable material that will ensure root systems are maintained in a moist, healthy condition.
2. Protect all plants with a tarpaulin when being transported in an open vehicle.
3. When approved by the Engineer, temporary storage of plants on the project site may be allowed. When temporary on-site storage is not approved, provide such facilities and location at no additional cost to the Contracting Authority.
4. During temporary storage, heel-in plants and maintain them by providing moist straw, moss, or other suitable material to protect root systems; watering; and protecting from excessive sun, wind, and inclement weather conditions. This will provide a healthy, vigorous plant when planted.

B. Allowable Planting Dates.

Install plant material during the following times:

1. **Evergreen Plants:** September 1 to October 15 and prior to June 1, but not after candles exceed 1 inch.

2. **Deciduous Plants (Balled and Burlapped and Container):** September 15 to November 15 and in the spring prior to June 1.
3. **Deciduous Plants (Bare Root):** In the spring prior to May 15.
4. **Weather Restrictions:** Planting may be conducted under unseasonable conditions, except in weather below 32°F or above 90°F. No variance from plant warranty or other requirements will be given for plants installed outside the specified periods.

C. Preparation.

1. Provide notice to the Engineer 3 days prior to planting.
2. All plants will be inspected by the Engineer prior to planting. Plants may be inspected and approved at the place of growth by the Engineer for compliance with the specifications for quality, size, and variety. Such approval does not waive the right to reject any plant material after it has been delivered to the site and/or installed.
3. Provide barriers or fencing as approved by Engineer to protect the public from injury when planting installation is within the right-of-way.

D. Location of Plants.

1. Mark the location of all plants with flags or lathe according to the contract documents. Mark trees individually. Stake the outline of bedded plants or shrub groups for the quantity on the plans without marking individual plants. The Engineer will approve the locations marked prior to excavation of planting pits and tree drainage wells.
2. Make field adjustments in plant locations where underground or overhead obstruction is encountered, or where changes have been made as approved by the Engineer.

E. Excavation of Planting Pit.

1. Excavate the plant pit, centered at the location marks, cylindrical in shape with a diameter 1 1/2 to 2 times larger than ball or root condition, with vertical sides and flat or saucer-shaped bottom. Excavate plant pit to a depth to match the nursery grade of the root crown for all balled and container root systems. Excavate plant pit to a depth 6 inches deeper for bare-rooted systems.
2. Scarify sides of excavated pit.
3. Following excavation of planting pit for all trees, fill the pit full of water; allow to stand (without adding water) for an 18 hour period to determine porosity of the soil.
4. If the Engineer determines the soils are too impervious, provide a planting well.

F. Planting.

1. **Balled and Burlapped and Container Plants.**
 - a. Ensure root systems are moist at the time of planting.
 - b. Remove all ties and wrap from branch system, except plant identification.
 - c. **Container Plants.**
 - 1) Remove plant root system carefully from container prior to planting without disturbance to root systems.
 - 2) Inspect root system and cut any circled (girdled) roots.

- 3) Place plants centered, upright, plumb, and with desired orientation in planting pit with the root crown matching existing grade.

d. Balled and Burlapped Plants.

- 1) Place plants centered, upright, plumb, and with desired orientation in planting pit with the root crown matching existing grade.
 - 2) After plant placement, cut and remove burlap from root ball.
- e. Carefully place and compact backfill material in layers, filling all voids until two thirds of plant pit is complete; fill pit with water and allow soil to settle.
 - f. Lightly compact the settled topsoil.
 - g. Continue placing backfill material and form a 3 inch deep saucer around plant.
 - h. Water plant and surrounding area until thoroughly moist.

2. Planting on Slopes.

- a. Place the top of the root crown at or slightly above the finished grade at the center of the planting pit.
- b. For all plants planted on significant slope, form a saucer as a dam or shoulder on the downhill side to catch and hold water and to discourage erosion.

G. Mulching.

1. Dig edges of mulched areas to ensure the top of the mulch at the edge of the planting area matches the existing ground surface.
2. Place mulch 3 inches deep in the planting saucer within 2 calendar days of planting.
3. Mulch an 18-inch radius area around tree trunks and shrub branch lines.
4. Provide a continuous mulch area around plant groupings.
5. Following mulch placement, pull mulch back 1 to 2 inches from the base of all trees and shrubs to allow air circulation.
6. Thoroughly water mulched areas. Rake to a smooth finished surface.

H. Wrapping.

1. When specified in the contract documents, wrap the trunk of deciduous trees in the fall of the year in which the tree is planted.
2. Inspect the trunk for injuries and evidence of insect infestation prior to wrapping.
3. Wrap trunks spirally from ground line by overlapping one-half of the tree wrapping material and completely cover trunk to the height of the first branch.
4. If necessary, secure wrapping material with twine or paper tape wound spirally downward in opposite direction, with ties around tree in at least three places in addition to top and bottom.
5. Remove wrapping material by April 1 of the next spring.

I. Pruning.

1. **General.**
 - a. Provide proper and sharp pruning tools to provide a clean cut without injuring the branch collar.

- b. Prune in such a manner as to retain the natural shape of the plant. Do not prune the terminal leader of a plant. Leave no protruding stubs, and prune to the closest outward growing bud.
- c. Plant materials incorrectly pruned will be rejected.

2. Deciduous Trees.

- a. Prune broken, damaged, or otherwise defective branches. Remove all branches that may not develop properly. Also, eliminate narrow crotches or competing leaders.
- b. Prune to develop an upright leader that will promote the symmetry of the tree. Prune flowering or specimen trees to develop their natural form.

3. Evergreen Trees and Shrubs: Remove dead and broken branches.

4. Deciduous Shrubs: Remove dead or irregular branches.

J. Clean Up.

- 1. Perform cleaning during installation and upon completion of work.
- 2. Remove all excess materials, trimmings, branches, soils, debris, and equipment from the site.
- 3. Repair any damage resulting from planting operations.
- 4. Clean all paved areas with a broom.
- 5. Remove all tags and labels from plants following acceptance by the Engineer.

K. Establishment Period and Acceptance.

- 1. **Establishment Period:** The plant establishment period is 1 year after the installation is accepted by the Engineer. A plant inspection will be made by the Engineer prior to the expiration of the establishment period.
- 2. **Maintenance:** Care for all plants during the period between the transport and storage of plants on or off site to acceptance of plant material and their installation as required to keep plants in a live, healthy growing condition.
 - a. Prune plants to maintain a desirable shape.
 - b. Remove weeds and grasses from planting beds and mulch areas. Apply herbicide to control weed growth when directed by the Engineer.
 - c. Water as required to enhance early root growth and maintain a moist soil.
 - d. Adjust stakes and ties to maintain plant in an upright and plumb condition.
 - e. Re-set settled plants to proper grades and position. Restore planting saucer and mulch; add backfill material and mulch as may be required.
 - f. Apply appropriate insecticides and fungicides necessary to maintain plants free of insects and disease.
- 3. **Plant Condition:** Ensure all plants are in a live, healthy, and growing condition both at the date of acceptance of the installation by the Engineer, and at the end of the 1 year plant establishment period.
- 4. **Replacement:** Replace all plants not found to be in a live, healthy, and growing condition during inspection at the 1 year establishment period at no additional cost to the Contracting Authority.

- a. Upon notice from Engineer, remove rejected plants from the site and replace with plant material of the same species and size as originally specified. Install replacement plants complying with the contract documents.
- b. Plants damaged due to fire or flooding beyond the contractors control or ice storms, hail, tornados, or acts of vandalism do not require replacement.

PART 4 METHOD OF MEASUREMENT.

- A. The Engineer will count each tree, shrub, perennial, grass, or ground cover plant installed in an acceptable manner.
- B. The Engineer shall measure installed Spaded Edge, As Per Plan on a lineal feet basis.
- C. The Engineer shall measure installed Rock Mulch, As per plan per square yards.
- D. The Engineer shall measure installed Mulch, Shredded Bark per cubic yards.

PART 5 BASIS OF PAYMENT.

- A. Payment will be at the unit price for each tree, shrub, or ground cover plant.

Unit price includes, but is not limited to, delivery, planting layouts, excavation, installation, placing backfill material, wrapping, staking or guying, herbicide, watering and maintenance during the period from purchasing and transport of the plant material until engineer approved installation. Mulching and Spaded Edge are included with other bid items.
- B. Payment will be at the unit price for each lineal foot of Spaded Edge. Unit price includes, but is not limited to layout, excavation, and installation with a motorized planting bed edger.
- C. Payment will be at the unit price per square yard of installed Rock Mulch. Unit price includes, but is not limited to, delivery, layout, excavation, and installation.
- D. Payment will be at the unit price per cubic yard of installed Shredded Hardwood Bark Mulch. Unit price includes, but is not limited to, delivery, layout, excavation, and installation.