



**SPECIAL PROVISIONS
FOR
WOOD PICKET FENCE**

**Linn County
TAP-U-1187(799)--8I-57**

**Effective Date
September 21, 2021**

THE STANDARD SPECIFICATIONS, SERIES 2015, ARE AMENDED BY THE FOLLOWING MODIFICATIONS AND ADDITIONS. THESE ARE SPECIAL PROVISIONS AND THEY SHALL PREVAIL OVER THOSE PUBLISHED IN THE STANDARD SPECIFICATIONS.

157165.01 DESCRIPTION.

- A.** This section covers the furnishing of all labor, materials, tools, equipment and performance of all work and services necessary or incidental for the installation of the wood picket fence as indicated on the plans or as specified herein.
- B.** This work shall consist of furnishing and installing wood picket fence as shown in the plans and as specified herein.

157165.02 MATERIALS.

A. General.

- 1.** Fence materials, layout, and appearance shall match the existing fence at each respective property. General product requirements are listed below, but the Contractor is responsible for evaluating the existing remaining fence ends to ensure uniformity and compatibility where the proposed fence ties into the existing fence.
- 2.** All components shall be manufactured and assembled and rated for 24 hours/365 days a year outdoor use in local weather conditions.
- 3.** The entire system shall have a minimum 3 year warranty.

B. Pickets.

Match existing wood materials, 72 inches high, 5.5 inches wide, and 0.5 inches thick, dog ear cut on top.

C. Posts.

Match existing wood materials, 108 inches high, 4 inches wide, 4 inches thick. 36 inches of post

shall be buried underground.

D. Backer Rails.

Match existing wood materials, 2 inches wide, 3 inches thick, three each per height of fence to match existing.

157165.03 CONSTRUCTION.

A. Construction Requirements.

1. Fence materials, layout, and appearance shall match the existing fence at each respective property. General installation requirements are listed in this Special Provision; however, the Contractor is responsible for evaluating the uniformity where the proposed fence ties into the existing remaining fence corners.
2. Place pickets on the outside of the fence, facing the adjoining right-of-way. Match existing picket spacing and gapping between each picket.
3. Install posts with uniform spacing on the inside of the fence. Posts shall be set with 36 inches of post buried underground. Post shall be set to plumb vertical and perpendicular to the backer rails.
4. Install three backer rails along the inside of the fence. Match the spacing of the backer rails on the existing fence. Backer rails shall be set to level horizontal and perpendicular to the posts.

B. Coordination.

It shall be the sole responsibility of the Contractor to coordinate among suppliers and contractors providing labor and equipment for the wood picket fence construction.

157165.04 METHOD OF MEASUREMENT.

Measurement will be in lineal feet of fence, measured along the bottom of the fence.

157165.05 BASIS OF PAYMENT.

- A. Payment will be at the contract unit price per lineal foot of fence installed.
- B. Unit price includes posts, backer rails, pickets, excavation of post holes, backfill of post holes, all hardware, all labor, materials, and equipment necessary for installation of the wood picket fence.